

# HE Windows 2000, Xp, Vista and 7 Driver

1w0300929 Rev3 2011-11-03









## 1. Introduction

### 1.1. Scope

This document should provide information needed to install the USB drivers for Telit modules.

### 1.2. Audience

This User Guide is intended for users who need to install and use one of Telit HE modems.

### 1.3. Contact Information, Support

Our aim is to make this guide as helpful as possible. Keep us informed of your comments and suggestions for improvements.

For general contact, technical support, report documentation errors and to order manuals, contact Telit's Technical Support Center at:

EMEA: [TS-EMEA@telit.com](mailto:TS-EMEA@telit.com)

NorthAmerica: [TS-NorthAmerica@telit.com](mailto:TS-NorthAmerica@telit.com)

LatinAmerica: [TS-LATINAMERICA@telit.com](mailto:TS-LATINAMERICA@telit.com)

APAC: [TS-APAC@telit.com](mailto:TS-APAC@telit.com)

Telit: <http://www.telit.com/en/products/technical-support-center/contact.php>

Telit appreciates feedback from the users of our information.

### 1.4. Product Overview

HE863 and HE910 modules contain a fully featured HSPA modem and UMTS/GSM/GPRS module.

### 1.5. Document Organization

This manual contains the following chapters:



- "Chapter 1, Introduction" provides a scope for this manual, target audience, technical contact information, and text conventions.
- "Chapter 2, Requisites" describes requisites for install Telit HE863 or HE910 USB driver in a PC with Windows 2000, XP, Vista and 7 OS installed.
- "Chapter 3, USB Driver download and Installation" describes how to add the Telit HE863 or HE910 USB driver in a PC with Windows 2000, XP, Vista and 7 OS installed.
- "Chapter 4, Dial-Up Connection" describes how to use the Telit HE863 or HE910 USB driver for start a dial-up connection.

## 1.6. Text Conventions

This section lists the paragraph and font styles used for the various types of information presented in this user guide.

| Format           | Content   |
|------------------|---|
| Arial monospaced | Filesystem paths, and Windows Xp, Vista and 7 OS menu items |





### 3. USB driver download and installation


#### 3.1. Installation

The following list of files needs to be available on the PC used for the installation procedure:

- TelitUSBInstaller\_x.xx.xx.zip (x.xx.xx depends on the version)

To install the USB driver follow these steps:

1. Download driver archive and uncompress it in a specific directory (e.g. c:\Telit\_Usb\_driver) where the installer executable can be found
2. If connected, disconnect the HE module from the PC. If installed, uninstall previous versions of the driver using following steps:
  - a. Start -> ControlPanel;
  - b. Double click on "Add or Remove Programs";
  - c. Scroll down until "Windows Driver Package - Telit (Telit\_XXX)..."









- d) Telit Mobile (USB3)
- e) Telit Mobile (USB4)
- f) Telit Mobile (USB5)
- g) Telit Mobile (USB6)

## 3.2. Disabling USB IMEI identification

By default each time a device with a different IMEI is connected, the operating system will require searching for the drivers and will create a new set of ports (with different COM enumeration).


For disabling this behaviour double click on the file `Telit_disable_USB_IMEI_identification.reg`, found inside the installation package, **before installing the driver** (if already installed, uninstall it and reinstall after adding the required registry keys).

For enabling again this behaviour uninstall the driver, double click on the file `Telit_enable_USB_IMEI_identification.reg` and reinstall the driver.






2. Click on "Create a connection to the network at your workspace"




3. Tick "Dial-up connection" checkbox, then click "Next".



4. Check the “Modem – Telit Mobile Highspeed Modem” then click “Next” checkbox.
5. Type a name for the new connection then click “Next”



6. Type the phone number “\*99#” then click “Next”.




7. Tick “Do not use my smart card” radio button then click “Next”





## 4.2. Connect using Dial-Up (USB mode)

To connect using the Dial-Up click twice on the icon in the desktop,



or click Start→Connect to→HE Terminal



Click "Dial" in "Connect HE Terminal" window





